

3M 2105 (Clear) Polyethylene Protective Tapes

Category : Polymer , Adhesive

Material Notes:

3M™ Polyethylene Protective Tapes 2105 has a very low-tack adhesive system to helpInformation provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-2105-Clear-Polyethylene-Protective-Tapes.php

| Physical Properties | Metric | English | Comments |
|---------------------|--------------|----------|------------|
| Thickness | 50.8 microns | 2.00 mil | ASTM D3652 |

| Mechanical Properties | Metric | English | Comments |
|---------------------------|-------------|-----------|-------------------------------|
| Tensile Strength at Break | 1.70 MPa | 247 psi | ASTM D3759 |
| Elongation at Break | 450 % | 450 % | ASTM D3759 |
| Peel Strength | 0.0219 kN/m | 0.125 pli | Adhesion to Steel; ASTM D3330 |

| Descriptive Properties | Value | Comments |
|------------------------|---------|----------|
| Adhesive Type | Acrylic | |
| Appearance | Clear | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China