

## 3M 2A10 Co-Extruded Polyethylene Protective Tapes

Category : Polymer , Adhesive

**Material Notes:**

3M™ Co-Extruded Polyethylene Protective Tapes have a low-tack adhesive system to help provide temporary protection for a variety of surface protection applications. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-2A10-Co-Extruded-Polyethylene-Protective-Tapes.php](http://www.lookpolymers.com/polymer_3M-2A10-Co-Extruded-Polyethylene-Protective-Tapes.php)

| Physical Properties | Metric       | English  | Comments   |
|---------------------|--------------|----------|------------|
| Thickness           | 50.8 microns | 2.00 mil | ASTM D3652 |

| Mechanical Properties     | Metric      | English   | Comments                      |
|---------------------------|-------------|-----------|-------------------------------|
| Tensile Strength at Break | 3.10 MPa    | 450 psi   | ASTM D882                     |
| Elongation at Break       | 600 %       | 600 %     | ASTM D882                     |
| Peel Strength             | 0.0219 kN/m | 0.125 pli | Adhesion to Steel; ASTM D3330 |

| Descriptive Properties | Value   | Comments |
|------------------------|---------|----------|
| Adhesive Type          | Acrylic |          |
| Appearance             | Clear   |          |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China