

3M 2A825 High Performance Temporary Surface Protection Tape

Category : Polymer , Adhesive

Material Notes:

3M™ High Performance Temporary Surface Protection Tape 2A825 is a very low adhesion temporary protection tape designed for a variety of surface protection applications. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-2A825-High-Performance-Temporary-Surface-Protection-Tape.php

| Physical Properties | Metric | English | Comments |
|---------------------|--------------|----------|------------|
| Thickness | 50.8 microns | 2.00 mil | ASTM D3652 |

| Mechanical Properties | Metric | English | Comments |
|---------------------------|--------------|------------|-------------------------------|
| Tensile Strength at Break | 31.0 MPa | 4500 psi | ASTM D3759 |
| Elongation at Break | 600 % | 600 % | ASTM D3759 |
| Peel Strength | 0.07669 kN/m | 0.4375 pli | Adhesion to Steel; ASTM D3330 |

| Descriptive Properties | Value | Comments |
|------------------------|---------------|----------|
| Adhesive Type | Acrylic-Based | |
| Appearance | Clear | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China