

## 3M 3383 Premium Performance Aluminum Foil Tape

Category : Metal , Nonferrous Metal , Aluminum Alloy , Polymer , Tape

**Material Notes:**

66 lb. moisture stable liner. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-3383-Premium-Performance-Aluminum-Foil-Tape.php](http://www.lookpolymers.com/polymer_3M-3383-Premium-Performance-Aluminum-Foil-Tape.php)

Physical Properties	Metric	English	Comments
Thickness	127 microns	5.00 mil	Backing; ASTM D3652
	178 microns	7.00 mil	Total; ASTM D3652

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	49.2 MPa	7140 psi	ASTM D3759
Peel Strength	0.49303 kN/m	2.8125 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	
Minimum Service Temperature, Air	-34.0 °C	-29.2 °F	

Descriptive Properties	Value	Comments
Adhesive Type	Acrylic	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China