

## 3M 413DL Flexomount™ Solid Printing Tapes

Category: Polymer, Adhesive

## **Material Notes:**

3M™ Flexomount™ Solid Printing Tapes are double coated tapes designed for mounting photopolymer and rubber printing plates to flexographic printing cylinders or sleeve systems. The adhesive systems are specially formulated for clean removability from both the plate and the print cylinder. Flexomount tapes have a solid vinyl carrier which is designed for printing solids and line work. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer\_3M-413DL-Flexomount-Solid-Printing-Tapes.php

Physical Properties	Metric	English	Comments
Density	1.06 g/cc	0.0383 lb/in³	
Thickness	102 microns	4.00 mil	Paper Liner
	102 microns	4.00 mil	Poly Liner
	508 microns	20.0 mil	Таре

Mechanical Properties	Metric	English	Comments
Peel Strength	0.27391 kN/m	1.5625 pli	Composite Sleeve, Adhesion; ASTM D3330
	0.351 kN/m	2.00 pli	Photopolymer, Adhesion; ASTM D3330
	0.438 kN/m	2.50 pli	Stainless Steel, Adhesion; ASTM D3330
	0.5478 kN/m	3.125 pli	Rubber, Adhesion; ASTM D3330

Processing Properties	Metric	English	Comments
Shelf Life	12.0 Month	12.0 Month	

Descriptive Properties	Value	Comments
Adhesive Type	Rubber Firm	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058



Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China