

## 3M 463 Adhesive Transfer Tape with 3M Adhesive 400

Category: Polymer, Adhesive

## **Material Notes:**

3M<sup>™</sup> Adhesive Transfer Tapes 463, 465, 9457 and 9665 with 3M<sup>™</sup> Adhesive 400 are ideal for bonding together a wide variety of similar and dissimilar materials such as metals, glass, wood, papers, paints, and many plastics. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer\_3M-463-Adhesive-Transfer-Tape-with-3M-Adhesive-400.php

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	Tape Only
	102 microns	4.00 mil	Release Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.27391 kN/m	1.5625 pli	to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	82.0 °C	180 °F	Long term
	121 °C	250 °F	Short term

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Carrier	None	
Adhesive Type	400	
Liner	60# Unbleached Densified Kraft	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China