

## 3M 469 Splicing Tapes

Category : Polymer , Adhesive

**Material Notes:**

3M™ Splicing Tapes utilize on acrylic pressure sensitive adhesive system that offers a balance of initial adhesion and good holding power. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-469-Splicing-Tapes.php](http://www.lookpolymers.com/polymer_3M-469-Splicing-Tapes.php)

Physical Properties	Metric	English	Comments
Thickness	127 microns	5.00 mil	Release Liner
	140 microns	5.50 mil	Tape

Mechanical Properties	Metric	English	Comments
Peel Strength	0.657 kN/m	3.75 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	9.00 °C	48.2 °F	Short term
	180 °C	356 °F	Long term

Descriptive Properties	Value	Comments
Adhesive Type	330	
Appearance	Light Red	
Liner	72# Densified Kraft	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China