

3M 551 Polyurethane Adhesive Sealant

Category : Polymer , Thermoset , Polyurethane, TS , Thermoset Polyurethane, Adhesive

Material Notes:

3M™ 500-Series Polyurethane Construction Sealant, Polyurethane Sealant and Polyurethane Adhesive Sealant products are one component, moisture curing products which form permanent elastic bonds. They bond to a wide variety of materials including plastics, metals, fiberglass, and wood. They are formulated to have a wide variety of Shore A hardness, open times, and performance parameters to meet many application needs. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-551-Polyurethane-Adhesive-Sealant.php

Physical Properties	Metric	English	Comments
Density	1.17 g/cc	0.0423 lb/in ³	
Volatile Organic Compounds (VOC) Content	36.5 g/l	36.5 g/l	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	45	45	ASTM C661
Tensile Strength at Break	3.10 MPa	450 psi	ASTM D412
Elongation at Break	>= 600 %	>= 600 %	ASTM D412
100% Modulus	0.00130 GPa	0.189 ksi	ASTM D412

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	90.0 °C	194 °F	
Minimum Service Temperature, Air	-40.0 °C	-40.0 °F	

Processing Properties	Metric	English	Comments
Cure Time	120 - 180 min	2.00 - 3.00 hour	Tack-Free, 50% RH
	1440 min	24.0 hour	Rate of Cure, 50% RH

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China