

## 3M 6035PC 12030 Polyurethane Foam Tape (15 lb./ft3 (239 kg/m3) Series)

Category : Polymer , Adhesive

### Material Notes:

3M™ series polyurethane foam substrates with a high performance, pressure-sensitive acrylic adhesive on one side. 3M™ microcellular polyurethane foam is designed for high performance gasketing and sealing applications. Has excellent resistance to compression set and die cuts cleanly. 3M™ acrylic adhesive provides an excellent bond to various surfaces and has good shear strength at elevated temperatures. Available in 15 lb/ft3 and 20 lb/ft3 densities. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-6035PC-12030-Polyurethane-Foam-Tape-15-lbft3-239-kgm3-Series.php](http://www.lookpolymers.com/polymer_3M-6035PC-12030-Polyurethane-Foam-Tape-15-lbft3-239-kgm3-Series.php)

Physical Properties	Metric	English	Comments
Water Absorption	4.0 %	4.0 %	ASTMD570

Mechanical Properties	Metric	English	Comments
Elongation at Break	90 %	90 %	ASTMD3574-E Die E
Compressive Strength	2.10 MPa	305 psi	Force Deflection; ASTMD3574-D
Tear Strength	0.700 kN/m	4.00 pli	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	107 °C	225 °F	
Minimum Service Temperature, Air	-40.0 °C	-40.0 °F	

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China