

3M 665 Repositionable Tape

Category : Polymer , Adhesive

Material Notes:

3M™ Repositionable Tapes are double coated tapes that are ideal for applications where one or both parts need to be repositioned or removed easily. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-665-Repositionable-Tape.php

Physical Properties	Metric	English	Comments
Thickness	35.6 microns	1.40 mil	Carrier
	88.9 microns	3.50 mil	Tape

Mechanical Properties	Metric	English	Comments
Peel Strength	0.25199 kN/m	1.4375 pli	Steel, 180° Peel, 72 hr dwell, Backside; ASTM D3330
	0.27391 kN/m	1.5625 pli	Steel, 180° Peel, 72 hr dwell, Faceside; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	52.0 °C	126 °F	

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Carrier	UPVC	
Adhesive Type	Backside	
	Faceside	
Appearance	Clear	
Liner	None	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China