

## **3M 7238 HP Indigo Optimized Polyester Label Product**

Category: Polymer, Adhesive

## **Material Notes:**

3M™ HP Indigo Optimized Polyester Label Products are durable, high performance materials that offer excellent thermal stability and moisture resistance. These polyester labels utilize 3M™ Adhesive P1400, which is a high performance tackified acrylic designed for use in demanding environments. These products are optimized for use in the HP Indigo printing press. All products are pattern coated with a dry edge (no adhesive) to minimize adhesive ooze and press clean-up.Information provided by 3M

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_3M-7238-HP-Indigo-Optimized-Polyester-Label-Product.php

Physical Properties	Metric	English	Comments
Thickness	22.9 microns	0.900 mil	Adhesive
	50.8 microns	2.00 mil	Facestock
	78.7 microns	3.10 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.386 kN/m	2.20 pli	180° Peel, 12"/min., 1" wide sample; TLMI Method

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	49.0 °C	120 °F	Application
	150 °C	302 °F	Service
Minimum Service Temperature, Air	-29.0 °C	-20.2 °F	Service
	-12.0 °C	10.4 °F	Application

Processing Properties	Metric	English	Comments
Shelf Life	12.0 Month	12.0 Month	

Descriptive Properties	Value	Comments
Adhesive Type	P1400 Perm	
Liner	50# SC Remoist	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com



Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China