

3M 766 Hazard Marking Vinyl Tape

Category : Polymer , Tape

Material Notes:

3M™ Hazard Marking Vinyl Tape 766 can be used in non-critical applications. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-766-Hazard-Marking-Vinyl-Tape.php

Physical Properties	Metric	English	Comments
Thickness	127 microns	5.00 mil	ASTM D3752

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	18.24 MPa	2645 psi	ASTM D3759
Elongation at Break	180 %	180 %	ASTM D3759
Peel Strength	0.1972 kN/m	1.125 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	29.0 °C	84.2 °F	
Minimum Service Temperature, Air	16.0 °C	60.8 °F	

Descriptive Properties	Value	Comments
Adhesive Type	Rubber	
Appearance	Black and yellow stripes	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China