

3M 7733FLW Overlaminating Film

Category : Polymer , Adhesive

Material Notes:

3M™ Overlaminating Film 7733FLW utilizes a clear polyester film that is recommended for optimum durability and superior outdoor UV exposure and print fade protection. 3M™ Adhesive 400 offers excellent low temperature performance and long term aging for resistance to yellowing in outdoor applications. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-7733FLW-Overlaminating-Film.php

Physical Properties	Metric	English	Comments
Thickness	20.3 microns	0.800 mil	Adhesive
	25.4 microns	1.00 mil	Facestock
	38.1 microns	1.50 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.263 kN/m	1.50 pli	180° Peel, 12"/min., 1" wide sample; TLMI Method

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	121 °C	250 °F	Service
Minimum Service Temperature, Air	-29.0 °C	-20.2 °F	Service
	-12.0 °C	10.4 °F	Application

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Type	400 Acrylic	
Appearance	Clear Polyester Liner	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China