3M 8067 All Weather Flashing Tape

Category : Polymer , Adhesive

Material Notes:

3M[™] All Weather Flashing Tape 8067 is a self-adhered, waterproof flashing membrane designed for sealing around openings and penetrations in exterior walls. This product has a unique acrylic pressure sensitive adhesive that aggressively sticks and stays stuck both at lower and higher application temperatures that traditional flashing tapes. It even adheres to damp surfaces. The proprietary backing seals around hand driven nails and staples to prevent moisture intrusion. This backing is also tough, resists punctures and tears yet it is thin to fit conveniently into corners and under siding. The split paper release liner provides fast application with easy and accurate positioning of the tape.Information provided by 3M

Order this product through the following link: http://www.lookpolymers.com/polymer_3M-8067-All-Weather-Flashing-Tape.php

Mechanical Properties	Metric	English	Comments
Peel Strength	0.5478 kN/m	3.125 pli	Adhesion to Housewrap; ASTM D3330
	0.657 kN/m	3.75 pli	Adhesion to Polyethylene; ASTM D3330
	0.657 kN/m	3.75 pli	Adhesion to OSB; ASTM D3330
	0.657 kN/m	3.75 pli	Adhesion to Anodized Aluminum, after UV exposure; ASTM D3330
	0.71216 kN/m	4.0625 pli	Adhesion to Anodized Aluminum, after 7 days in water; ASTM D3330
	0.82172 kN/m	4.6875 pli	Adhesion to Anodized Aluminum, after thermal cycling; ASTM D3330
	0.7669 kN/m	4.375 pli	Adhesion to Anodized Aluminum; ASTM D3330
	@Temperature 80.0 °C, Time 605000 sec	@Temperature 176 °F, Time 168 hour	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	49.0 °C	120 °F	Application
	80.0 °C	176 °F	Service
Minimum Service Temperature, Air	-40.0 °C	-40.0 °F	Service
	-18.0 °C	-0.400 °F	Application

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com



Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China