

3M 9415PC Repositionable Tape

Category : Polymer , Adhesive

Material Notes:

3M™ Repositionable Tapes are double coated tapes that are ideal for applications where one or both parts need to be repositioned or removed easily. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-9415PC-Repositionable-Tape.php

Physical Properties	Metric	English	Comments
Thickness	25.4 microns	1.00 mil	Carrier
	50.8 microns	2.00 mil	Tape
	142 microns	5.60 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.03287 kN/m	0.1875 pli	Steel, 180° Peel, 72 hr dwell, Backside; ASTM D3330
	0.5478 kN/m	3.125 pli	Steel, 180° Peel, 72 hr dwell, Faceside; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	70.0 °C	158 °F	

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Carrier	Clear Polyester	
Adhesive Type	Backside	
	Faceside	
Appearance	Translucent	
Liner	70# White Polycoated Kraft	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China