

3M 9425HT Repositionable Tape

Category : Polymer , Adhesive

Material Notes:

3M™ Repositionable Tapes are double coated tapes that are ideal for applications where one or both parts need to be repositioned or removed easily. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-9425HT-Repositionable-Tape.php

Physical Properties	Metric	English	Comments
Thickness	25.4 microns	1.00 mil	Carrier
	107 microns	4.20 mil	Liner
	137 microns	5.40 mil	Tape

Mechanical Properties	Metric	English	Comments
Peel Strength	0.131 kN/m	0.750 pli	Steel, 180° Peel, 72 hr dwell, Backside; ASTM D3330
	0.49303 kN/m	2.8125 pli	Steel, 180° Peel, 72 hr dwell, Faceside; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	121 °C	250 °F	

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Carrier	Clear Polyester	
Adhesive Type	Backside	
	Faceside	
Appearance	Clear	
Liner	58# Natural Polycoated Kraft	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China