

## 3M 9449S Repositionable Tape

Category: Polymer, Adhesive

**Material Notes:** 

3M™ Repositionable Tapes are double coated tapes that are ideal for applications where one or both parts need to be repositioned or removed easily. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer\_3M-9449S-Repositionable-Tape.php

Physical Properties	Metric	English	Comments
Thickness	10.2 microns	0.400 mil	Таре
	63.5 microns	2.50 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.05478 kN/m	0.3125 pli	Steel, 180° Peel, 72 hr dwell, Faceside; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	70.0 °C	158 °F	

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Carrier	None	
Adhesive Type	Faceside	
Appearance	Translucent	
Liner	55# Densified Kraft Paper	

## Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China