

3M 9459W Laminating Adhesive For Label Component Systems

Category : Polymer , Adhesive

Material Notes:

3M™ Adhesive Transfer Tape 9459W is a high Performance 300 Adhesive with 55 lb Densified Paper Kraft Paper Liner. 1.5 mil Thick with 3.2 mil Liner Features: Bond high and low surface energy plastics, textured plastics, foams, fabrics and coated papers. White version of 3M Adhesive Transfer Tape 9459S High opacity General Industrial Applications, Transportation, Automotive, Appliance Adhering, joining, affixing, bonding, mounting, holding, and attaching. HSE and some LSE material Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-9459W-Laminating-Adhesive-For-Label-Component-Systems.php

Physical Properties	Metric	English	Comments
Thickness	38.1 microns	1.50 mil	Adhesive
	81.3 microns	3.20 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.1972 kN/m	1.125 pli	to Polypropylene, 2 mil polyester, 72 hr Dwell; ASTM D3330
	0.29582 kN/m	1.6875 pli	to stainless steel, 90° peel, 12 in./min, 2 mil polyester, 20 min Dwell; ASTM D3330
	0.351 kN/m	2.00 pli	to stainless steel, 2 mil polyester, 72 hr Dwell; ASTM D3330
	0.3725 kN/m	2.125 pli	to Polycarbonate, 2 mil polyester, 72 hr Dwell; ASTM D3330

Processing Properties	Metric	English	Comments
Shelf Life	12.0 Month	12.0 Month	

Descriptive Properties	Value	Comments
Appearance	White	
Liner	55# Densified Kraft	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China