

3M 9497 Splicing Tape

Category : Polymer , Adhesive

Material Notes:

3M™ Splicing Tapes utilize an acrylic pressure sensitive adhesive system that offers a balance of initial adhesion and good holding power. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-9497-Splicing-Tape.php

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	Tape Only
	76.2 microns	3.00 mil	Release Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.49303 kN/m	2.8125 pli	to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	121 °C	250 °F	Long term
	177 °C	351 °F	Short term

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Carrier	Polyester Film	
Adhesive Type	430	
Appearance	Clear	
Liner	Tan 60# Densified Kraft	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China