

## 3M 9576R Splicing Tape

Category : Polymer , Tape

### Material Notes:

3M™ Splicing Tape offers excellent flying splice and core starting wet grab characteristics. They are typically used in the printing industry and perform well at process speeds in excess of 2000 feet per minute and can be used through ovens up to 232°C if dwell times are ten seconds or less. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-9576R-Splicing-Tape.php](http://www.lookpolymers.com/polymer_3M-9576R-Splicing-Tape.php)

Physical Properties	Metric	English	Comments
Thickness	102 microns	4.00 mil	Tape
	102 microns	4.00 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.657 kN/m	3.75 pli	180° peel, Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	50.0 °C	122 °F	Long term
	75.0 °C	167 °F	Short term

Descriptive Properties	Value	Comments
Adhesive Type	400	
Appearance	Red	
Liner	60# Densified Kraft Paper, Tan	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China