

3M 9672LE Adhesive Transfer Tapes with Adhesive 300LSE

Category : Polymer , Adhesive

Material Notes:

3M™ Adhesive Transfer Tapes with 3M™ Low Surface Energy Acrylic Adhesive 300LSE provides high bond strength to most surfaces, including many low surface energy plastics such as polypropylene and powder coated paints. The acrylic adhesive also provides excellent adhesion to surfaces contaminated lightly with oil typically used with machine parts. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-9672LE-Adhesive-Transfer-Tapes-with-Adhesive-300LSE.php

Physical Properties	Metric	English	Comments
Thickness	127 microns	5.00 mil	Adhesive
	157 microns	6.20 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	1.118 kN/m	6.375 pli	ABS, 90° peel, 2 mil aluminum backing, 15 min RT; ASTM D3330
	1.1942 kN/m	6.8125 pli	Stainless Steel, 90° peel, 2 mil aluminum backing, 15 min RT; ASTM D3330
	1.2600 kN/m	7.1875 pli	Polypropylene, 90° peel, 2 mil aluminum backing, 15 min RT; ASTM D3330
	1.40 kN/m	8.00 pli	ABS, 90° peel, 2 mil aluminum backing, 72 hr RT; ASTM D3330
	1.49 kN/m	8.50 pli	Polypropylene, 90° peel, 2 mil aluminum backing, 72 hr RT; ASTM D3330
	1.53 kN/m	8.75 pli	Stainless Steel, 90° peel, 2 mil aluminum backing, 72 hr RT; ASTM D3330

Descriptive Properties	Value	Comments
Liner	83# Polycoated kraft	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China