

3M Controltac™ 3500C Changeable Graphic Film with Comply™ Adhesive

Category : Polymer , Film

Material Notes:

4-mil, opaque white vinyl film with a matte finish; Excellent hiding power; Pressure-activated adhesive for easy sliding, tacking, snap up and repositioning; Air release channels for fast, easy, bubble-free graphic installation and changeable for clean removable without heat or chemicals
Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Controltac-3500C-Changeable-Graphic-Film-with-Comply-Adhesive.php

Physical Properties	Metric	English	Comments
Thickness	102 microns	4.00 mil	without adhesive
	114 - 127 microns	4.50 - 5.00 mil	with adhesive

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	>= 23.3 MPa	>= 3380 psi	
Peel Strength	0.105 kN/m	0.600 pli	Adhesion to Fruehauf pre-painted panels
	0.316 kN/m	1.80 pli	Adhesion to Aluminum, anodized

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	38.0 °C	100 °F	
Minimum Service Temperature, Air	-2.00 °C	28.4 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China