

## 3M Controltac™ 3545C Removable Graphic Film with Comply™ Adhesive

Category : Polymer , Film

**Material Notes:**

4-mil white, opaque, polyolefin film; Chloride-free film; Pressure-activated adhesive for easy sliding, tacking, snap up and repositioning; Air release channels for fast and easy application; Removable with heat Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-Controltac-3545C-Removable-Graphic-Film-with-Comply-Adhesive.php](http://www.lookpolymers.com/polymer_3M-Controltac-3545C-Removable-Graphic-Film-with-Comply-Adhesive.php)

Physical Properties	Metric	English	Comments
Thickness	102 microns	4.00 mil	without adhesive
	114 - 127 microns	4.50 - 5.00 mil	with adhesive

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	13.8 MPa	2000 psi	
Peel Strength	0.193 - 0.228 kN/m	1.10 - 1.30 pli	Adhesion to Fruehauf pre-painted panels
	0.351 - 0.403 kN/m	2.00 - 2.30 pli	Adhesion to Aluminum, anodized

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	38.0 °C	100 °F	
Minimum Service Temperature, Air	4.00 °C	39.2 °F	

### Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China