

## 3M Controltac™ 3552C Changeable Graphic Film with Comply™ Adhesive

Category : Polymer , Film

### Material Notes:

2-mil white, vinyl film; Pressure-activated adhesive for easy sliding, tacking, snap up and repositioning; Conforms to surfaces with corrugations and rivets; Air release channels for fast, easy, bubble-free installations and Removable without heat or chemicals Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-Controltac-3552C-Changeable-Graphic-Film-with-Comply-Adhesive.php](http://www.lookpolymers.com/polymer_3M-Controltac-3552C-Changeable-Graphic-Film-with-Comply-Adhesive.php)

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	without adhesive
	76.2 - 102 microns	3.00 - 4.00 mil	with adhesive

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	>= 17.2 MPa	>= 2490 psi	
Peel Strength	0.105 kN/m	0.600 pli	Adhesion to Glass
	0.298 kN/m	1.70 pli	Adhesion to Fruehauf pre-painted panels
	0.666 kN/m	3.80 pli	Adhesion to ABS

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	38.0 °C	100 °F	Flat surfaces with and without rivets
	38.0 °C	100 °F	Cured surfaces
Minimum Service Temperature, Air	2.00 °C	35.6 °F	Flat surfaces with and without rivets
	15.0 °C	59.0 °F	Cured surfaces

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China