

3M Controltac™ 8655C ES Changeable Graphic Film with Comply™ Adhesive

Category : Polymer , Film

Material Notes:

3M™ Controlact™ Plus Changeable Graphic Film with Comply™ Adhesive 8655C ES combines the features found in Controltac and Comply adhesive technologies, including pressure activation, positionability and air release channels, for the fastest and easiest bubble-free graphic installations. This 4-mil film, designed for electrostatic imaging, is ideal for short-term removable graphics for fleet or commercial vehicles and indoor or outdoor graphic applications. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Controltac-8655C-ES-Changeable-Graphic-Film-with-Comply-Adhesive.php

Physical Properties	Metric	English	Comments
Thickness	102 microns	4.00 mil	without adhesive
	114 - 127 microns	4.50 - 5.00 mil	with adhesive

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	>= 23.3 MPa	>= 3380 psi	
Peel Strength	0.105 kN/m	0.600 pli	Adhesion to Fruehauf pre-painted panels
	0.316 kN/m	1.80 pli	Adhesion to Aluminum, anodized

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	38.0 °C	100 °F	
Minimum Service Temperature, Air	-2.00 °C	28.4 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China