

3M Controltac™ IJ380Cv3 Wrap Film with Comply™ v3 Adhesive

Category: Polymer, Film

Material Notes:

2-mil white, vinyl film with a luster finish; Pressure-activated adhesive for easy sliding, tacking, snap up and repositioning; Non-visible, air release channels for fast, easy, bubble-free installations; Superior conformability and lift resistance; perfect for vehicle wraps with deep channels or concave areas-Stretch selected finished graphic constructions up to 150% (ie a 10 in film piece can stretch to 15 inches) without primer or relief cuts and maintain lift resistance; see details and exceptions in Section 10; Removable with heat and/or chemicalsInformation provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Controltac-IJ380Cv3-Wrap-Film-with-Comply-v3-Adhesive.php

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	without adhesive
	76.2 - 102 microns	3.00 - 4.00 mil	with adhesive

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	13.8 MPa	2000 psi	
Peel Strength	0.526 - 0.877 kN/m	3.00 - 5.00 pli	Adhesion to Automotive clear coats
	0.701 - 0.877 kN/m	4.00 - 5.00 pli	Adhesion to ABS
	0.701 - 0.877 kN/m	4.00 - 5.00 pli	Adhesion to Acrylic enamel
	1.23 - 1.40 kN/m	7.00 - 8.00 pli	Adhesion to Aluminum, anodized

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China