

3M Dyneon™ TF 5032 PTFE Dispersion (discontinued **)

Category : Polymer , Thermoplastic , Fluoropolymer , PTFE

Material Notes:

Used for impregnation. Dyneon PTFE dispersions are aqueous dispersions developed for use in metal coating formulations and for application of impregnation and fabric coating applications. A range of products are offered to meet the variety of requirements for particle size, emulsifier type and content, and solids level. Data provided by Dyneon.

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Dyneon-TF-5032-PTFE-Dispersion-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	1.50 g/cc	0.0542 lb/in ³	hydrometer
Solids Content	60 %	60 %	ASTM D4441
Particle Size	160 µm	160 µm	ISO 13321
pH	8.5	8.5	ASTM D4441
Viscosity	22 cP	22 cP	D=30/s; DIN 54 453

Descriptive Properties	Value	Comments
Emulsifier Content	5%	ASTM D4441
Emulsifier Type	non-ionic	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China