

## 3M Dyneon™ TF 5035 PTFE Dispersion (discontinued \*\*)

Category : Polymer , Thermoplastic , Fluoropolymer , PTFE

### Material Notes:

Used for metal coatings; impregnation. Dyneon PTFE dispersions are aqueous dispersions developed for use in metal coating formulations and for application of impregnation and fabric coating applications. A range of products are offered to meet the variety of requirements for particle size, emulsifier type and content, and solids level. Data provided by Dyneon.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-Dyneon-TF-5035-PTFE-Dispersion-nbspdiscontinued-.php](http://www.lookpolymers.com/polymer_3M-Dyneon-TF-5035-PTFE-Dispersion-nbspdiscontinued-.php)

Physical Properties	Metric	English	Comments
Density	1.50 g/cc	0.0542 lb/in <sup>3</sup>	hydrometer
Solids Content	58 %	58 %	ASTM D4441
Particle Size	225 µm	225 µm	ISO 143321
pH	8.5	8.5	ASTM D4441
Viscosity	14 cP	14 cP	D=30/s; DIN 54 453

Descriptive Properties	Value	Comments
Emulsifier Content	5%	
Emulsifier Type	non-ionic	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China