

## 3M FA03E Matte Clear Acetate Label Products

Category : Polymer , Adhesive

### Material Notes:

3M™ Matte Clear Acetate Label Products offer consistent, high quality film appearance. This film die-cuts easily which helps extend die life in comparison with polyester label stocks. These acetate labels utilize 3M™ Adhesive P1212, which is a high clarity general purpose acrylic emulsion for use on overlamination and decorative films that exhibits good initial tack, excellent die cutting properties, minimal cold flow, and good UV resistance. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-FA03E-Matte-Clear-Acetate-Label-Products.php](http://www.lookpolymers.com/polymer_3M-FA03E-Matte-Clear-Acetate-Label-Products.php)

| Physical Properties | Metric       | English  | Comments  |
|---------------------|--------------|----------|-----------|
| Thickness           | 50.8 microns | 2.00 mil | Facestock |
|                     | 78.7 microns | 3.10 mil | Liner     |

| Mechanical Properties | Metric     | English  | Comments                                         |
|-----------------------|------------|----------|--------------------------------------------------|
| Peel Strength         | 0.526 kN/m | 3.00 pli | 180° Peel, 12"/min., 1" wide sample; TLMI Method |

| Thermal Properties               | Metric   | English  | Comments    |
|----------------------------------|----------|----------|-------------|
| Maximum Service Temperature, Air | 49.0 °C  | 120 °F   | Application |
|                                  | 60.0 °C  | 140 °F   | Service     |
| Minimum Service Temperature, Air | -29.0 °C | -20.2 °F | Service     |
|                                  | 5.00 °C  | 41.0 °F  | Application |

| Processing Properties | Metric     | English    | Comments |
|-----------------------|------------|------------|----------|
| Shelf Life            | 24.0 Month | 24.0 Month |          |

| Descriptive Properties | Value         | Comments |
|------------------------|---------------|----------|
| Adhesive Type          | P1212 Perm 18 |          |
| Liner                  | 50# SC C2S    |          |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China