

3M FB 136 Fire Block Sealant

Category : Other Engineering Material

Material Notes:

3M Fire Block Sealant FB 136 is a one component, non-combustible draft, smoke and fireblocking sealant, designed to resist high temperatures and smoke passage in non-rated construction. Fire Block Sealant FB 136 meets ASTM E-136, current 2003 International Building Code (IBC), 2003 International Residential Code (IRC), 2003 International Residential Mechanical Code, 2003 International Fuel Gas Code and NFPA 5000 draft, smoke and fireblocking requirements. This material features superior adhesion strength, caulk rate and no sag application, plus a halogen-free formula. This material can be installed with a standard caulking gun, pneumatic pumping equipment or it can be easily applied with a putty knife or trowel. Fire Block Sealant FB 136 will bond to concrete, brick, metals, wood, plastic and cable jacketing. No mixing is required. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-FB-136-Fire-Block-Sealant.php

Physical Properties	Metric	English	Comments
Density	1.76 g/cc	0.0636 lb/in ³	
Solids Content	70 %	70 %	

Processing Properties	Metric	English	Comments
Cure Time	15.0 min	0.250 hour	ASTM C679

Descriptive Properties	Value	Comments
Appearance	Gray	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China