

## 3M FM0234R2 Clear Polyester Label Products

Category: Polymer, Adhesive

## **Material Notes:**

3M™ Clear Polyester Label Products are durable, high performance materials that offer excellent thermal stability and moisture resistance.

These label products utilize 3M™ Adhesive R3500, which is designed for use on smooth surfaces such as glass, metal and plastic (including polystyrene) and offers excellent UV resistance, good initial tack, and long term adhesion with clean removability and is an excellent alternative to static cling.Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer\_3M-FM0234R2-Clear-Polyester-Label-Products.php

Physical Properties	Metric	English	Comments
Thickness	25.4 microns	1.00 mil	Facestock
	78.7 microns	3.10 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.0526 kN/m	0.300 pli	180° Peel, 12"/min., 1" wide sample; TLMI Method

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	43.0 °C	109 °F	Application
	68.0 °C	154 °F	Service
Minimum Service Temperature, Air	-29.0 °C	-20.2 °F	Service
	5.00 °C	41.0 °F	Application

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Type	R3500 Rem 16	
Liner	50# SC Remoist	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842



Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China