

3M FM04630K White Polyester Label Product

Category : Polymer , Adhesive

Material Notes:

3M™ White Polyester Label Products FM046302 and FM04630K are durable, high performance materials that offer excellent thermal stability and moisture resistance. These label products utilize 3M™ Adhesive P1480, which is a high performance tackified acrylic formulated for acid resistance and adhesion to polyolefins. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-FM04630K-White-Polyester-Label-Product.php

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	Facestock
	150 microns	5.90 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.877 kN/m	5.00 pli	180° Peel, 12"/min., 1" wide sample; TLMI Method

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	49.0 °C	120 °F	Application
	150 °C	302 °F	Service
Minimum Service Temperature, Air	-30.0 °C	-22.0 °F	Service
	5.00 °C	41.0 °F	Application

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Type	P1480 Perm. 24	
Liner	83# Laser	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China