

3M FM298 Indoor UL Recognized Clear Polyester Overlaminate Label Products

Category: Polymer, Adhesive

Material Notes:

3M™ Indoor UL Recognized Clear Polyester Overlaminate Label Products are durable, high performance materials that offer excellent thermal stability and moisture resistance. These polyester overlaminate labels utilize 3M™ Adhesive P1212, which is a high clarity general purpose acrylic emulsion that exhibits good initial tack, excellent die cutting properties, minimal cold flow, and good UV resistance. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-FM298-Indoor-UL-Recognized-Clear-Polyester-Overlaminate-Label-Products.php

Physical Properties	Metric	English	Comments
Thickness	76.2 microns	3.00 mil	Facestock
	78.7 microns	3.10 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.526 kN/m	3.00 pli	180° Peel 12"/min, 1" wide sample; TLMI Method

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	49.0 °C	120 °F	Service
	125 °C	257 °F	Application
Minimum Service Temperature, Air	-29.0 °C	-20.2 °F	Application
	5.00 °C	41.0 °F	Service

Descriptive Properties	Value	Comments
Adhesive Type	P1212 Perm 18	
Liner	44# Poly/kraft	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Address: United North Road 215, Fengxian District, Shanghai City, China

Skype: lookpolymers