

## 3M FP029202 White Polypropylene Label Product

Category : Polymer , Adhesive

**Material Notes:**

3M™ White Polypropylene Label Products FP02750N and FP029202 offer excellent durability and moisture resistance. These label products utilize 3M™ Adhesive P1480 which is a high performance tackified acrylic formulated for acid resistance and adhesion to polyolefins. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-FP029202-White-Polypropylene-Label-Product.php](http://www.lookpolymers.com/polymer_3M-FP029202-White-Polypropylene-Label-Product.php)

Physical Properties	Metric	English	Comments
Thickness	66.0 microns	2.60 mil	Facestock
	78.7 microns	3.10 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.877 kN/m	5.00 pli	180° Peel, 12"/min., 1" wide sample; TLMI Method

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	49.0 °C	120 °F	Application
	60.0 °C	140 °F	Service
Minimum Service Temperature, Air	-29.0 °C	-20.2 °F	Service
	5.00 °C	41.0 °F	Application

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Type	P1480 Perm 30	
Appearance	50# SC Remoist	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China