

## **3M FV092 Soft Translucent Vinyl Label Products**

Category: Polymer, Adhesive

## **Material Notes:**

3M<sup>™</sup> Soft Translucent Vinyl Label Products are flexible, conformable vinyl label stocks that offer durability and moisture resistance. These vinyl labels utilize 3M<sup>™</sup> Adhesive P1212, which is a high clarity general purpose acrylic emulsion that exhibits good initial tack, excellent die cutting properties, minimal cold flow, and good UV resistance. Information provided by 3M

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_3M-FV092-Soft-Translucent-Vinyl-Label-Products.php

Physical Properties	Metric	English	Comments
Thickness	78.7 microns	3.10 mil	Liner
	88.9 microns	3.50 mil	Facestock

Mechanical Properties	Metric	English	Comments
Peel Strength	0.526 kN/m	3.00 pli	180° Peel, 12"/min., 1" wide sample; TLMI Method

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	49.0 °C	120 °F	Application
	60.0 °C	140 °F	Service
Minimum Service Temperature, Air	-29.0 °C	-20.2 °F	Service
	5.00 °C	41.0 °F	Application

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Type	P1212 Perm 18	
Liner	50# SC	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058



Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China