

3M FVT30 Tire Label Product

Category : Polymer , Adhesive

Material Notes:

3M™ Tire Label Products utilize a flexible and conformable white vinyl labelstock that offers durability, moisture resistance, and dimensional stability. 3M™ Adhesive G1120, a rubber-based aggressive adhesive for use in tire label applications. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-FVT30-Tire-Label-Product.php

Physical Properties	Metric	English	Comments
Thickness	88.9 microns	3.50 mil	Facestock

Mechanical Properties	Metric	English	Comments
Peel Strength	0.701 kN/m	4.00 pli	180° Peel, 12"/min., 1" wide sample; TLMI Method

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	49.0 °C	120 °F	Application
	60.0 °C	140 °F	Service
Minimum Service Temperature, Air	-29.0 °C	-20.2 °F	Service
	5.00 °C	41.0 °F	Application

Processing Properties	Metric	English	Comments
Shelf Life	6.00 Month	6.00 Month	

Descriptive Properties	Value	Comments
Adhesive Type	G1120 Tire 30	
Appearance	50# SC Remoist	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China