

3M GM630 Very Soft Gripping Material

Category: Polymer, Adhesive

Material Notes:

3M™ Gripping Materials are based on 3M's proprietary micro-replicated technology. 3M gripping materials consist of a high-friction surface developed to enhance grip and reduce slippage. The plain backed versions have a nylon knit backing that provides stretch in the cross-web direction; it would typically be attached to other substrates by sewing. It is ideally suited for applications requiring some stretch, such as work or athletic gloves. The adhesive backed 3M gripping materials have the same high-friction surface with a thin flexible backing laminated with an acrylic pressure sensitive adhesive which is good for low surface energy surfaces. These gripping products are designed to be used along, or as a two-part mated system. When used alone on a single surface, 3M soft gripping material holds, it releases just as easily.Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-GM630-Very-Soft-Gripping-Material.php

Physical Properties	Metric	English	Comments
Thickness	20.3 microns	0.800 mil	
Vapor Pressure	<= 0.000 bar	<= 0.000 torr	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	>= 30	>= 30	
Coefficient of Friction	3.0	3.0	wet, kinetic
	3.3	3.3	dry, kinetic
Abrasion	75	75	[%], Taber, CS-10 500 g, Stem damage; ASTM D3389

Thermal Properties	Metric	English	Comments	
Maximum Service Temperature, Air	71.0 °C	160 °F		
Minimum Service Temperature, Air	-40.0 °C	-40.0 °F		

Descriptive Properties	Value	Comments
Adhesive Carrier	Nylon knit	
Appearance	Dark Gray	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com



Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China