

3M Novec™ 72DA Engineered Fluid

Category : Fluid

Material Notes:

3M™ Novec™ 72DA is ideal for flux removal and vapor degreasing operations. It is non-flammable and low in toxicity which makes it an ideal replacement for chlorinated solvents such as Trichloroethylene (TCE) and for n-propyl bromide (nPB). Feature and Benefits: Non-flammable Non-conductive Low toxicity Low Global Warming Potential (GWP) Zero ozone depletion potential Low surface tension penetrates tight spaces for improved cleaning Excellent for removal of ionic contamination Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Novec-72DA-Engineered-Fluid.php

Physical Properties	Metric	English	Comments
Density	1.27 g/cc	0.0459 lb/in ³	Liquid
Viscosity	0.40 cP	0.40 cP	
Vapor Pressure	0.480 bar	360 torr	
Surface Tension	18 dynes/cm	18 dynes/cm	

Thermal Properties	Metric	English	Comments
Heat of Vaporization	251.2 J/g	108.1 BTU/lb	
Boiling Point	44.0 °C	111 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China