

3M OFM0103 Outdoor UL Recognized Polyester Overlamine Label Products

Category : Polymer , Adhesive

Material Notes:

3M™ Outdoor UL Recognized Polyester Overlamine Label Products are durable high performance clear materials that offer excellent thermal stability, abrasion and moisture resistance. These polyester labels utilize 3M™ Adhesive P1400 which is a high performance tackified acrylic designed for use in demanding environments. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-OFM0103-Outdoor-UL-Recognized-Polyester-Overlamine-Label-Products.php

| Physical Properties | Metric | English | Comments |
|---------------------|--------------|----------|-----------|
| Thickness | 25.4 microns | 1.00 mil | Facestock |
| | 117 microns | 4.60 mil | Liner |

| Mechanical Properties | Metric | English | Comments |
|-----------------------|------------|----------|--|
| Peel Strength | 0.386 kN/m | 2.20 pli | 180° Peel 12"/min, 1" wide sample; TLMI Method |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|----------|----------|-------------|
| Maximum Service Temperature, Air | 49.0 °C | 120 °F | Service |
| | 125 °C | 257 °F | Application |
| Minimum Service Temperature, Air | -29.0 °C | -20.2 °F | Application |
| | 5.00 °C | 41.0 °F | Service |

| Descriptive Properties | Value | Comments |
|------------------------|---------------|----------|
| Adhesive Type | P1400 Perm 16 | |
| Liner | 78# White CCK | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China