

3M OFM0109 Outdoor UL Recognized Polyester Overlaminate Label Products

Category: Polymer, Adhesive

Material Notes:

3M™ Outdoor UL Recognized Polyester Overlaminate Label Products are durable high performance clear materials that offer excellent thermal stability, abrasion and moisture resistance. These polyester labels utilize 3M™ Adhesive P1400 which is a high performance tackified acrylic designed for use in demanding environments. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-OFM0109-Outdoor-UL-Recognized-Polyester-Overlaminate-Label-Products.php

Physical Properties	Metric	English	Comments
Thickness	25.4 microns	1.00 mil	Facestock
	38.1 microns	1.50 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.386 kN/m	2.20 pli	180° Peel 12"/min, 1" wide sample; TLMI Method

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	49.0 °C	120 °F	Service
	125 °C	257 °F	Application
Minimum Service Temperature, Air	-29.0 °C	-20.2 °F	Application
	5.00 °C	41.0 °F	Service

Descriptive Properties	Value	Comments
Adhesive Type	P1400 Perm 16	
Liner	Clear Polyester Liner	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China