

3M P590 Fritted Glass Primer

Category : Other Engineering Material , Additive/Filler for Polymer

Material Notes:

3M™ Adhesion Promoter AP596 and 3M™ Primers P590, P591, P592, P595 and P597 are low viscosity adhesion promoters recommended for use with the 3M™ 500-Series Polyurethane Adhesives/Sealants and 3M™ 700-Series Hybrid Adhesives/Sealants, as well as the 3M™ OEM Polyurethane Glass Adhesive Sealant 590. 3M Adhesion Promoter and Primers are applied to a wide variety of materials including glass, acrylic / PMMA, polycarbonate, and many other materials prior to adhesive/sealant use to assist in bonding. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-P590-Fritted-Glass-Primer.php

| Physical Properties | Metric | English | Comments |
|--|---------|---------|----------|
| Solids Content | 28.5 % | 28.5 % | |
| Volatile Organic Compounds (VOC) Content | 687 g/l | 687 g/l | |

| Processing Properties | Metric | English | Comments |
|-----------------------|------------|------------|----------|
| Shelf Life | 12.0 Month | 12.0 Month | |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| Appearance | Black | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China