

## 3M P595 Teak & Glass Primer

Category: Other Engineering Material, Additive/Filler for Polymer

## **Material Notes:**

3M<sup>™</sup> Adhesion Promoter AP596 and 3M<sup>™</sup> Primers P590, P591, P592, P595 and P597 are low viscosity adhesion promoters recommended for use with the 3M<sup>™</sup> 500-Series Polyurethane Adhesives/Sealants and 3M<sup>™</sup> 700-Series Hybrid Adhesives/Sealants, as well as the 3M<sup>™</sup> OEM Polyurethane Glass Adhesive Sealant 590. 3M Adhesion Promoter and Primers are applied to a wide variety of materials including glass, acrylic / PMMA, polycarbonate, and many other materials prior to adhesive/sealant use to assist in bonding.Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer\_3M-P595-Teak-Glass-Primer.php

Physical Properties	Metric	English	Comments
Solids Content	29.5 %	29.5 %	
Volatile Organic Compounds (VOC) Content	693 g/l	693 g/l	
Viscosity	50 cP	50 cP	

Processing Properties	Metric	English	Comments
Shelf Life	12.0 Month	12.0 Month	

Descriptive Properties	Value	Comments
Appearance	Black	

## Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China