

3M Scotch® 353 High Performance Box Sealing Tape

Category: Polymer, Adhesive

Material Notes:

Scotch® Box Sealing Tape 351 is a high performance packaging tape used for box sealing, splicing, recouperage and other demanding packaging applications. This product has a strong abrasion resistant backing and the most consistent pressure sensitive hot melt adhesive system available. This time proven construction assures high performance in a wide range of environments and applications. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotch-353-High-Performance-Box-Sealing-Tape.php

Physical Properties	Metric	English	Comments
Thickness	25.4 microns	1.00 mil	Backing; ASTM D3652
	48.3 microns	1.90 mil	Total; ASTM D3652

Mechanical Properties	Metric	English	Comments
Elongation at Break	110 %	110 %	ASTM D3759
Peel Strength	0.49303 kN/m	2.8125 pli	Adhesion to Steel; ASTM D3330
Film Tensile Strength at Break, MD	9.10 MPa	1320 psi	ASTM D3759
Film Tensile Strength at Break, TD	10.9 MPa	1590 psi	ASTM D3759

Descriptive Properties	Value	Comments
Adhesive Type	Pressure sensitive hot melt rubber-resin	
Appearance	Clear and tan	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China