

3M Scotch® 3785 Performance Continuous Taping System Tape

Category : Polymer , Adhesive

Material Notes:

Scotch® Performance Continuous Taping System Tapes 3785 is a packaging tape used for box sealing and specially designed for use with the 3M-Matic™ Continuous Taping System (CTS) stand. These tapes have a strong, conformable backing and a consistent pressure sensitive hot melt adhesive system. This time-proven construction assures a reliable performance in a wide range of environments and applications. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotch-3785-Performance-Continuous-Taping-System-Tape.php

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	Backing; ASTM D3652
	78.7 microns	3.10 mil	Total; ASTM D3652

Mechanical Properties	Metric	English	Comments
Elongation at Break	160 %	160 %	ASTM D3759
Peel Strength	0.60259 kN/m	3.4375 pli	Adhesion to Steel; ASTM D3330
Film Tensile Strength at Break, MD	7.76 MPa	1130 psi	ASTM D3759
Film Tensile Strength at Break, TD	15.5 MPa	2250 psi	ASTM D3759

Descriptive Properties	Value	Comments
Adhesive Type	Pressure sensitive rubber resin	
Appearance	Clear	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China