

## 3M Scotch-Seal™ 2084 Metal Sealant

Category: Polymer

## **Material Notes:**

Features: 3M™ Scotch-Seal™ Metal Sealant 2084 is a one-part aluminum colored sealant which air dries to a tough, flexible film that resists water, oils and fuel. Retains sealing properties after extended aging. Can be used to bond and seal aluminum to glass; also adheres well to many other metals and woods. Metal sealant 2084, conforms to requirements of AAMA Specification 801.1 (Architectural Aluminum Manufacturers Association Specification title "Adhesive Type Sealant for Joints of Applied or Integral Fin.")Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer\_3M-Scotch-Seal-2084-Metal-Sealant.php

Physical Properties	Metric	English	Comments
Solids Content	40 - 47 %	40 - 47 %	
Brookfield Viscosity	7000 - 22500 cP	7000 - 22500 cP	RVF #6 sp. @ 20 rpm

Mechanical Properties	Metric	English	Comments
Peel Strength	4.38 kN/m	25.0 pli	180°, Canvas to aluminum, pulled at 2"/min

Thermal Properties	Metric	English	Comments
Flash Point	-18.0 °C	-0.400 °F	

Processing Properties	Metric	English	Comments
Cure Time	5.00 min	0.0833 hour	Tack Free Time
Shelf Life	15.0 Month	15.0 Month	

Descriptive Properties	Value	Comments
Drying time	24 hrs	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China