

3M Scotch-Weld™ Hi-Strength Laminating 92 Cylinder Spray Adhesive

Category : Polymer , Adhesive

Material Notes:

A high performance, high temperature resistant, tack industrial grade spray adhesive designed for use in a wide variety of applications. Features: It can be used for high pressure laminate, veneers, fiberglass, headliners, soft foams, fabrics, cork, tile, rubber and steel any many other materials. Formulated with exceptionally high solids. A fast tacking adhesive. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotch-Weld-Hi-Strength-Laminating-92-Cylinder-Spray-Adhesive.php

Physical Properties	Metric	English	Comments
Density	0.815 g/cc	0.0294 lb/in ³	
Solids Content	23 %	23 %	
Volatile Organic Compounds (VOC) Content	577 g/l	577 g/l	

Descriptive Properties	Value	Comments
Appearance	Translucent and Red	
Base	Synthetic Elastomer	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China