

## 3M Scotch-Weld™ SI1500 Surface Insensitive Instant Adhesive

Category: Polymer, Adhesive

## **Material Notes:**

3M™ Scotch-Weld™ Surface Insensitive Adhesives bond rough, porous, contaminated, and acidic substrates including wood, cardboard, veneer, fabric, cork, and leather. SI1500 is a surface insensitive cyanoacrylate that has high viscosity and has excellent gap filling capabilities. It relies less on surface moisture for cure speed than standard cyanoacrylates. Information provided by 3M

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_3M-Scotch-Weld-SI1500-Surface-Insensitive-Instant-Adhesive.php

Physical Properties	Metric	English	Comments
Density	1.08 g/cc	0.0390 lb/in³	Uncured
Brookfield Viscosity	1275 - 1650 cP	1275 - 1650 cP	LVF, sp 3 @ 30 rpm

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	82.0 °C	180 °F	
Minimum Service Temperature, Air	-54.0 °C	-65.2 °F	

Processing Properties	Metric	English	Comments
Cure Time	0.0833 - 1.00 min	0.00139 - 0.0167 hour	Time to Handling Strength
	1440 min	24.0 hour	Full Cure

Descriptive Properties	Value	Comments
Appearance	Clear Liquid	

## Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China