

3M Scotchcal™ ElectroCut™ 7125-58 Graphic Film

Category : Polymer , Film

Material Notes:

2-mil cast vinyl in 61 colors; Pressure-sensitive, permanent adhesive; Same color on both sides; The blue paper liner on 7125-10 and 7125-20 provides easier visibility when weeding, other film colors have a white paper liner; Superior cutting as small as 0.375 in (0.95 cm) and weeding; Ideal for prespaced and electronically cut, screen printed or used in narrow width thermal transfer printing systems Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotchcal-ElectroCut-7125-58-Graphic-Film.php

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	without adhesive
	63.5 - 88.9 microns	2.50 - 3.50 mil	with adhesive

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	17.2 MPa	2490 psi	
Peel Strength	0.526 kN/m	3.00 pli	Adhesion to Polypropylene
	0.701 kN/m	4.00 pli	Adhesion to ABS
	0.701 kN/m	4.00 pli	Adhesion to Acrylic
	0.701 kN/m	4.00 pli	Adhesion to Acrylic enamel
	0.701 kN/m	4.00 pli	Adhesion to Fruehauf pre-painted panels
	0.701 kN/m	4.00 pli	Adhesion to Polycarbonate
	0.701 kN/m	4.00 pli	Adhesion to Urethane paints
	0.877 kN/m	5.00 pli	Adhesion to Chrome
	1.40 kN/m	8.00 pli	Adhesion to Aluminum, alodine

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	38.0 °C	100 °F	
Minimum Service Temperature, Air	10.0 °C	50.0 °F	

Descriptive Properties	Value	Comments
Appearance	Burgundy	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China