

## 3M Scotchkote™ 162CR Epoxy Coating

Category : Polymer , Thermoset , Epoxy

### Material Notes:

3M Scotchkote Epoxy Coating 162CR has been specifically developed as a 100% solids lining for eth internals of tanks, vessels and other equipment in contact with dirty water, mild aqueous chemicals and oils. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-Scotchkote-162CR-Epoxy-Coating.php](http://www.lookpolymers.com/polymer_3M-Scotchkote-162CR-Epoxy-Coating.php)

Physical Properties	Metric	English	Comments
Density	1.50 g/cc	0.0542 lb/in <sup>3</sup>	
Solids Content	100 %	100 %	
Thickness	254 microns	10.0 mil	

Processing Properties	Metric	English	Comments
Cure Time	180 - 240 min	3.00 - 4.00 hour	Touch Dry
	10100 min	168 hour	Full Cure

Descriptive Properties	Value	Comments
Appearance	Light Gray, Mid Gray and Red	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China