

3M Scotchkote™ FB856 Urethane Primer

Category : Polymer

Material Notes:

Scotchkote Urethane Primer FB 856 has been specifically developed as a primer/sealer for porous mineral, timber and asphalt surfaces used on floors and roofs. Product Features: Combines good application characteristics with fast drying capabilities. Designed for use prior to application of Scotchkote urethane finishes. Suitable for brush and roller application. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotchkote-FB856-Urethane-Primer.php

Physical Properties	Metric	English	Comments
Density	1.06 g/cc	0.0383 lb/in ³	
Solids Content	65 %	65 %	
Volatile Organic Compounds (VOC) Content	312 g/l	312 g/l	
Thickness	76.2 microns	3.00 mil	dry
	114 microns	4.50 mil	wet

Processing Properties	Metric	English	Comments
Cure Time	120 min	2.00 hour	Touch Dry

Descriptive Properties	Value	Comments
Appearance	Clear	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China